

N314X-8

Tour Grade

SCREW-ON

BOLT-ON



Audiophiles, prepare yourself for goosebumps. Eminence is revolutionizing the Pro Audio industry, again. Meet the latest in high frequency driver technology, the N314X-8. Utilizing an advanced new thin ply carbon material, combined with the latest FEA techniques, the N314X-8 delivers Beryllium like high frequency extension with a robustness that is unrivaled by any dome material out there. High speed of sound and acoustical figure of merit make this material a “no-brainer”. Couple that with unprecedented reliability compared to metal domes, and realize there is no better value in the world.

SPECIFICATION

Throat Size	1.4", 35.6 mm
Nominal Impedance*	8 Ω
Minimum Impedance	6.6 Ω @ 3.7 kHz
Power Rating*	150 W (AES)
Free Air Resonance	494 Hz
DC Resistance (Re)	4.8 Ω
Usable Frequency Range*	500 Hz - 20 kHz
Recommended Crossover	800 Hz / 12 dB
Sensitivity*	110.5 dB
Magnet Material	Neodymium
Magnet Weight	11 oz, 0.31 kg
Voice Coil Diameter	3", 76.2 mm
Voice Coil Former	Polyimide
Diaphragm Material	TeXtreme®

MOUNTING INFORMATION

Overall Diameter	5.72", 145.3 mm
Driver Volume Displaced	0.0234 cu.ft., 0.66 liters
Depth	2.53", 64.3 mm
Net Weight	5.1 lbs., 2.3 kg
Shipping Weight	5.3 lbs., 2.4 kg
Mounting Thread	N/A
Mounting Holes Diameter	4x 1/4-20
Mounting Holes B.C.D.	4", 101.6 mm

