

Mick Thomson Signature

DV-77

From the beginning, the focus of this speaker was balance, response, and a very musical tonality. Delivering tight punchy lows, thick harmonically complex mid-range & detailed highs without excess fizz. Not a clone or a copy, this speaker was designed in the studio and proven on stage

12" | 70 W 8 Ω



SPECIFICATION

MOUNTING INFORMATION

MATERIALS OF CONSTRUCTION

Nominal Basket Diameter	12.0", 305 mm	Enclosure Type		Copper voice coil
Nominal Impedance*	Ω 8	Closed Back		Nomex former
Watts	70 W	Open Back		Ferrite
Resonance	70 Hz	Driver Volume Displaced	0.079 cu.ft.,2.25 liters	
Usable Frequency Range	70 Hz - 5.3 kHz	Overall Diameter	12.24 ", 310.9 mm	Stamped steel basket
Sensitivity***	100.6 dB	Baffle Hole Diameter	11.09 ", 281.7 mm	Paper cone
Magnet Weight	50 oz.	Depth	5.19 ", 131.8 mm	Full molded paper
Gap Height	0.313 ", 8.0 mm	Front Sealing Gasket	Yes	Zurette dust cap
Voice Coil Diameter	1.75 ", 44 mm	Rear Sealing Gasket	Yes	
		Mounting Holes Diameter	0.13 ", 3.4 mm	
		Mounting Holes B.C.D.	11.69 ", 296.9 mm	
		Net Weight	10.40 lbs., 4.72 kg	
		Shipping Weight	12.10 lbs., 5.49 kg	





